TM SERIES 1/2" - 2" WATER METERS

ΤN	I S	ER	IES

TM SER	IES — SPECIFICA	TIONS	
Design Type:	Turbine		
Fitting Size:	1/2" 3/4"	1" 1-1/2" 2"	
Fitting Type:	Schedule 80 Spigo	t (Pipe) End or NPT (Female)	
Flow Range:			
1/2" - TM 050:	1 - 10 GPM (3.8 - 38 LPM)		
3/4" - TM075	2 - 20 GPM (7.6 - 76 LPM)		
1" - TM100: 1-1/2" - TM150	5 - 50 GPM (19 - 190 LPM) 10 - 100 GPM (38 - 380 LPM)		
2" - TM200	20 - 200 GPM (76 - 760 LPM)		
Accuracy:	± 3.0% of reading		
Pressure Rating:	225 PSIG / 15.3 BAR at 73° F (23° C)		
Operating Temperature:	+32° F to +140° F (0° to +60° C)		
Battery Life:	5 Years		
Wetted Materials:			
Housing:	PVC		
Bearings:			
Shaft:	Tungsten Carbide		
Rotor:	PVDF 316 Stainless Steel		
Rings:			
Shipping Weight (approx.):	Spigot	NPT	
1/2" - TM050:	.38 lbs. (.172 kg)	.55 lbs. (.249 kg)	
3/4" - TM075: 1" - TM100:	.43 lbs. (.304 kg) .49 lbs. (.222 kg)	.67 lbs. (.304 kg) .49 lbs. (.381 kg)	
1-1/2" - TM150:	.66 lbs. (.222 kg)	1.38 lbs. (.626 kg)	
2" - TM200:	.78 lbs. (.354 kg)	1.78 lbs. (.807 kg)	
Display Features:	(0)		
Dispidy realules.	Rate of Flow, Batch and Cumulative Totals, Field Calibration available		
Pulse Output:	Open Collector (NF	PN)	
	APPROVALS		
	(f		



TM Series Meters are designed for use in water applications. The five smallest sizes are shown here. (For 3" and 4" meters, see next page.) Choose either Spigot (pipe end) or NPT or fittings.

For complete part number, see "Number Reference" chart on page 46.

ACCURACY: ±3.0% READING

Features and Benefits:

- Easy to install.
- Displays in gallons, litres and cubic feet.
- Indicates Batch, Cumulative Totals and Rate of Flow.
- Available in NPT or Spigot fittings.
- Meets Schedule 80 specifications.
- Lithium battery life: 5 years.
- Non-volatile totals means amounts are retained when batteries are replaced or power is lost.





Applications:

- OEM water treatment equipment / skids
- Sub-metering of facility water usage
- Small waste water treatment equipment
- Water based cooling systems

Model TM050

"Look for the blue label!"