



AirGard® Air Flow Monitors



Model 315-BSC

Model 350-CEM

AirGard Air Flow Monitors Model 315-BSC

The Alnor® AirGard® Flow Monitor Model 315-BSC is a simple, go/no-go monitor for critical airflows including the downflow of a bio-safety cabinet. By warning of poor bio-safety cabinet performance, the 315-BSC can increase staff protection while reducing experiment contamination.

AirGard Air Flow Monitors Model 350-CEM

The Alnor® AirGard® Model Air Flow Monitor 350-CEM goes a step beyond the Model 315-BSC. Its large LED and digital display of measured velocity give unrivaled information to users, making this monitor a powerful diagnostic tool.

Features and Benefits (Both Models)

- Range 25-2,000 fpm (0.127-10.16 m/s)
- Accuracy $\pm 5\%$ of set point
- Visual display jumbo green, yellow, and red LEDs
- Alarm indications jumbo red LED, audible alarm, relay output
- Input power 9-30 V AC/DC
- Mounting flush or kit
- Agency listings CE
- Velocity readings taken by remote probe inserted in air flow stream

Features and Benefits (Model 350-CEM)

- Accuracy $\pm 5\%$ of reading or 5 fpm, whichever is greater
- Visual digital display bar graph with green, yellow, and red zones; jumbo green, yellow, and red LEDs

Rugged. Reliable. Professional.



AirGard Air Flow Monitors

Models 350-CEM and 315-BSC

Specifications

Models 350-CEM and 315-BSC

	AirGard 350-CEM	AirGard 315-BSC
Bar graph display range	25–2,000 fpm (0.13–10.2 m/s)	n/a
Alarm range	25–2,000 fpm (0.13–10.2 m/s)	25–2,000 fpm (0.13–10.2 m/s)
Alarm delays	user configurable through menu	3 seconds
Relay output	NC, NO	NC, NO
Remote alarm acknowledge	yes	no
Units	selectable (English & Metric)	n/a
Display–visual	bar graph, red zone–alarm, yellow zone–marginal, green zone–normal, jumbo LEDs (digital LCD can be enabled)	jumbo green LED for normal jumbo yellow LED for warning jumbo red LED for alarm
Alarm indications	jumbo red LED and audible alarm (85 dB @ 4" [10 cm])	jumbo red LED and audible alarm (85 dB @ 4" [10 cm])
High flow alarm disable	yes	n/a
Horn silence	temporary and permanent	temporary and permanent
Mounting	flush or kit	flush or kit
Cable length	10 ft (3 m)	10 ft (3 m)
Calibration	single point field calibration recommended	low alarm set point
Operating temperature	50–95°F (10–35°C)	50–95°F (10–35°C)
Storage temperature	-40–150°F (-40–65°C)	-40–150°F (-40–65°C)
Power requirement	9–30V AC/DC	9–30V AC/DC
Instrument dimensions front face plate	5.25" x 3.0" x 0.625" 13.3 cm x 7.62 cm x 1.59 cm	5.25" x 3.0" x 0.625" 13.3 cm x 7.62 cm x 1.59 cm
rear enclosure	3.0" x 2.0" x 0.5" 7.62 cm x 5.08 cm x 1.27 cm	3.0" x 2.0" x 0.5" 7.62 cm x 5.08 cm x 1.27 cm
Accuracy	±5% of reading or 5 fpm, whichever is greater	±5% of set point
Agency listings	CE	CE

Alnor Products, TSI Incorporated - 500 Cardigan Road Shoreview, MN 55126-3996 USA
USA Tel: +1 800 874 2811 E-mail: customerservice@alnor.com



Contact your local Alnor Distributor or visit our website www.alnor.com for more detailed specifications.